

PVC-seam-sealer

For sealing of welded seams of PVC –waterproofing geomembranes (e.g. ELBEblue line SBG, STG, ELBEsecur WTG, WTG, WTTG),

realizes a permanent composit with the installed geomembrane after evaporation of the solvent at atmospheric conditions

PRODUCT DESCRIPTION:

Basis: PVC-P in solution,
 Colour: variable
 Viscosity: viscous

HANDLING REFERENCES:

- stirring before usage
- thickened seam-sealer mastic can be replenished to serviceable consistency by addition of solution welding compound (THF)
- cans of seam-sealer are preserved always well enclosed
- basically all reinforced geomembranes have to be sealed at the weldseam-lines with sealing mastic, for homogene membranes a sealing is recommended as additional protection
- the treated seam must be dry, clean and free of fat and dust
- for application along the seam-line capillary flasks of PE can be used
- consumption is approximately 15 g/m seam

DANGER REFERENCES:

EUH019 May form explosive peroxides.

H225 Liquid and vapour highly flammable.

H302 Harmful to health if swallowed.

H319 Causes serious eye irritation.

H335+H336 May cause respiratory irritation. May cause drowsiness and dizziness.

H351 Suspected of causing cancer.

ASSURANCE REFERENCES:

P210 Keep away from heat/sparks/naked flames/hot surfaces. Do not smoke.

P241 Use explosion-proof electrical equipment/ventilation systems/lighting.

P261 Avoid inhalation of dust/smoke/gas/steam/vapour/aerosol.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground container and receiving equipment.

P303+P361+P353 UPON CONTACT WITH THE SKIN (or hair): Remove all contaminated items of clothing immediately. Shower/wash off skin with water.

P305+P351+P338 UPON CONTACT WITH THE EYES: Gently rinse for a few minutes with water. If possible remove any contact lenses. Rinse again.

P301+P312 IF SWALLOWED: In case of indisposition contact POISON INFORMATION CENTRE or a doctor.

P405 Keep locked away when in storage.

P501 Dispose of the contents/container in accordance with the local/regional/national/international regulations.

Storage:

Store in a place with a solvent-proof floor. Store sealed containers in a dry, cool and well-ventilated place (+15 to +25°C). Keep away from heat and ignition sources. Only store in the original container.



These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products at time of delivery. Always check validity of certificates. The customer/installer is responsible for the proper use and application of the product.

ELBTAL PLASTICS GmbH & Co. KG
 Grenzstraße 9, D-01640 Coswig
 Tel. +49 (0) 3523 5330 0
 Fax. +49 (0) 3523 5330 220
 www.elbtal-plastics.de